Total Quality. Assured.

Test Report Number: FJXT80165151

Applicant: XIAMEN GREEN MOUNTAIN IMP&EXP CO LTD IMPORT&EXPORT CO., LTD.
22/F., Building 2, Thaihot Plaza Xiufeng
Fuzhou 350012 Fujian China
Attn: lily

Date: May 13, 2026

Sample Description:
One (1) group of submitted sample said to be Black outsole.

Standard	:	--
Buyer's Name	:	--
Colour	:	Black
Vendor	:	--
Manufacturer	:	--
Supplier	:	--
Style No./Name	:	
P.O. No.	:	
Ref.	:	SNOWTRAX Rubber Outsole
Country Of Origin	:	
Goods Exported To	:	
Date Received/Date Test Started	:	Mar. 31, 2026
Date Final Information Confirmed	:	--

Authorized By:
For Intertek Testing Services Shenzhen Ltd.
Xiamen Branch

Peter Chen
Lab Supervisor

/lululin

深圳天祥质量技术服务有限公司厦门分公司
福建省厦门火炬高新区创新路 2 号兴联电子大厦一楼 2C 和四楼 4C、4D、4L，361006
Intertek Testing Services Shenzhen Ltd. Xiamen Branch
Unit 2C, 2/F. & Unit 4C/4D/4L,4/F, Xinglian Building, No. 2, Chuangxin Road, Huoju Hi-tech Zone, Xiamen, Fujian, China
Tel: +86 592 8063 389 Fax: +86 592 8060 054

INTERTEK TESTING SERVICES SHENZHEN LTD. XIAMEN BRANCH 检验检测专用章 (2)

Test Report Number: FJXT80165151

Conclusion:

Index	Test Item	Result
1.	Hardness	No Comment
2.	Hardness	No Comment
3.	Hardness	No Comment

Should you have any query on this report, you may contact at xmfootwear@intertek.com

Authorized By:
For Intertek Testing Services Shenzhen Ltd.
Xiamen Branch

Peter Chen
Lab Supervisor

/lululin

深圳天祥质量技术服务有限公司厦门分公司
福建省厦门火炬高新区创新路 2 号兴联电子大厦二楼 2C 和四楼 4C、4D、4L，361006
Intertek Testing Services Shenzhen Ltd. Xiamen Branch
Unit 2C, 2/F. & Unit 4C/4D/4L,4/F, Xinglian Building, No. 2, Chuangxin Road, Huoju Hi-tech Zone, Xiamen, Fujian, China
Tel: +86 592 8063 389 Fax: +86 592 8060 054

INTERTEK TESTING SERVICES SHENZHEN LTD. XIAMEN BRANCH (2)
检验检测专用章

Test Report Number: FJXT80165151

Tests Conducted (As Requested By The Applicant)

1 Hardness (SATRA TM205: 2016(2017), The Type Of Durometer: Shore A, Modify, -20° C)

Total Thickness:	6.17 mm
The Number Of Layers:	1 Layer
The Type Of Surface Tested:	Other
The Time Interval At Which The Indentation Hardness Reading Was Taken:	3 Seconds.
The Hardness Value:	51 Shore A

2 Hardness (SATRA TM205: 2016(2017), The Type Of Durometer: Shore A , Modify, -30° C)

Total Thickness:	6.19 mm
The Number Of Layers:	1 Layer
The Type Of Surface Tested:	Other
The Time Interval At Which The Indentation Hardness Reading Was Taken:	3 Seconds.
The Hardness Value:	52 Shore A

3 Hardness (SATRA TM205: 2016(2017), The Type Of Durometer: Shore A)

Total Thickness:	6.18 mm
The Number Of Layers:	1 Layer
The Type Of Surface Tested:	Other
The Time Interval At Which The Indentation Hardness Reading Was Taken:	3 Seconds.
The Hardness Value:	48 Shore A

End of Report

/ lululin

深圳天祥质量技术服务有限公司厦门分公司
福建省厦门火炬高新区创新路 2 号兴联电子大厦二楼 2C 和四楼 4C、4D、4L，361006
Intertek Testing Services Shenzhen Ltd. Xiamen Branch
Unit 2C, 2/F. & Unit 4C/4D/4L,4/F, Xinglian Building, No. 2, Chuangxin Road, Huoju Hi-tech Zone, Xiamen, Fujian, China
Tel: +86 592 8063 369 Fax: +86 592 8060 054

Total Quality. Assured.

Test Report Number: FJXT80165151

Tests Conducted (As Requested By The Applicant)

The statement of conformity in this report is based on the decision rules agreed upon by the Client. Intertek has taken into account the measurement uncertainty calculated by the laboratory. This applies only where no specific decision rules are defined by the Client, regulatory requirements, or standard specifications. Please note that the applied decision rule is applicable solely to numerical test results. For any other cases where specific decision rules have been established by the Client, regulations, or standards, those rules will take precedence over the general guidelines used herein.

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client, Intertek's responsibility and liability are limited to and subject to our standard Terms and Conditions which can be obtained at our website: http://www.intertek.com/terms/. Intertek assumes no liability to any party, other than to the Client in accordance with responsible for all the information provided in the reports, except when information is provided the agreement, for any loss, expense or damage occasioned by the use of this report, Intertek is responsible for all the information provided in the report, except when information is provided by the Client or when the Client requires the item to be tested acknowledging a deviation from specified conditions that can affect the validity of results.

All samples information provided in this report was submitted by the Client. The Client is solely responsible for the accuracy and completeness of the samples and associated information. The observations and test results in this report are relevant to the sample(s) tested and submitted by client, The report is not intended to be a recommendation for any particular course of action, you are responsible for acting as you see fit on the basis of the report results. This report does not discharge or release you from your legal obligations and duties to any other person.

Only the Client is authorized to permit copying or distribution of this report and the report shall not be reproduced except in full, Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek, This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

深圳天祥质量技术服务有限公司厦门分公司
福建省厦门火炬高新区创新路 2 号兴联电子大厦二楼 2C 和四楼 4C、4D、4L，361006
Intertek Testing Services Shenzhen Ltd. Xiamen Branch
Unit 2C, 2/F. & Unit 4C/4D/4L,4/F, Xinglian Building, No. 2, Chuangxin Road, Huoju Hi-tech Zone, Xiamen, Fujian, China
Tel: +86 592 8063 369 Fax: +86 592 8060 054

INTERTEK TESTING SERVICES SHENZHEN LTD. XIAMEN BRANCH 检验检测专用章 (2)



深圳天祥质量技术服务有限公司厦门分公司
福建省厦门火炬高新区创新路 2 号兴联电子大厦二楼 2C 和四楼 4C、4D、4L，361006
Intertek Testing Services Shenzhen Ltd. Xiamen Branch
Unit 2C, 2/F. & Unit 4C/4D/4L,4/F, Xinglian Building, No. 2, Chuangxin Road, Huoju Hi-tech Zone, Xiamen, Fujian, China
Tel: +86 592 8063 369 Fax: +86 592 8060 054